

SPECIFICATIONS



BASECOAT/ADHESIVE

A Basecoat and Adhesive for Foam Board Insulation and Masonry Trim Products

BASECOAT/ADHESIVE is a one component, dry, polymer modified, cementitious basecoat composed of sand, cement, proprietary chemicals, and polymer modifiers. BASECOAT/ADHESIVE is used for bonding and priming foam board prior to the application of thin brick. BASECOAT/ADHESIVE can also be used for adhering stone, concrete, tile and masonry trim products to autoclaved aerated concrete.

Specify for adhering stone, concrete, tile and masonry trim products to Autoclaved Aerated Concrete surfaces.

Specify for adhering foam board to autoclaved aerated concrete.

Specify for priming foam board prior to decorative finish applications.

Specify for above grade application.

DO NOT specify for coating below grade.

DO NOT specify for coating metal, glass, plastic, or wood.

PART 1: GENERAL

Submittals

- Product Data: Submit manufacturer's technical information and installation instructions for materials required.

Quality Assurance

- Provide all coatings, adhesives, and sealants from one source.
- Provide job site mock-up sample (2 ft. X 2 ft.)
- Sample to be accepted by architect/engineer prior to starting work.
- Remove sample when directed by architect/engineer.

Delivery, Storage and Handling

- Deliver and store packaged material in original containers, unopened. Prevent damage to materials from water, freezing, or other causes.
- Provide heated and dry storage conditions for materials at site.
- Remove unused materials and waste from project site.

Project Conditions

- Maintain environmental conditions and protect work during and after installation and comply with manufacturer's printed instructions.
- Maintain temperatures at not less than 40° F for a minimum of 48 hours after installation.
- Do not apply to frozen surfaces or surfaces containing frost.
- Do not apply when ambient temperature is above 110° F.

PART 2: PRODUCTS

Materials

- Use Old Mill Brick, Inc. BASECOAT/ADHESIVE and other approved products only

Coatings

- BASECOAT/ADHESIVE, as manufactured by Old Mill Brick, Inc.
- Use accessories as specified by manufacturer.

Mixing

- Use clean equipment for preparation. Only mix what can be used in a 45 minute period. Use cool clean potable water. Mix to a homogenous consistency adding small amounts of water to adjust workability. Let mixture stand for five minutes after initial mixing, stir again, adding small amounts of water for workability once only. Adhesive should be used immediately after mixing.

PART 3: EXECUTION**Inspection**

- Verify substrate surface is ready to receive installation of work.
- Verify that surfaces are free of dust, loose particles, oil, or other foreign materials.
- Do not proceed with work until surfaces and conditions comply with manufacturer's requirements.

Preparation

- Prepare substrate in accordance with manufacturer's instructions.

Installation

- Install coating in accordance with manufacturer's printed instructions.

Protection

- Protect surface from damage or contamination from foreign materials.
- Maintain protection until completion of work.

Cleaning

- Remove product and protective materials from job site.